

IMSA 19-1

14 AWG



Product Description: 2 or more conductors, insulated with PE twisted for maximum flexibility and jacketed with a high quality PVC, sunlight resistant, rated at 600V.

Color Code Chart 4
Voltage 600V
Temperature 75°C
Standard Black Jacket

Construction:

Bare copper conductors, polyethylene insulation and black PVC jacket. Indent printed. Twisted with an overall moisture resistant tape. Non wicking, non metallic moisture resistant fillers are used when needed.

P/N	AWG	# COND	STRAND	INS THICKNESS	JACKET THICKNESS	NOM DIA.
98021419-1	14	2	SOLID	.025	.045	.322
980214X19-1	14	2	STRANDED	.025	.045	.340
98031419-1	14	3	SOLID	.025	.045	.339
980314X19-1	14	3	STRANDED	.025	.045	.358
98041419-1	14	4	SOLID	.025	.045	.369
980414X19-1	14	4	STRANDED	.025	.045	.390
98051419-1	14	5	SOLID	.025	.045	.402
980514X19-1	14	5	STRANDED	.025	.045	.426
98071419-1	14	7	SOLID	.025	.045	.435
980714X19-1	14	7	STRANDED	.025	.045	.463
98091419-1	14	9	SOLID	.025	.060	.538
980914X19-1	14	9	STRANDED	.025	.060	.569
98101419-1	14	10	SOLID	.025	.060	.580
981014X19-1	14	10	STRANDED	.025	.060	.616
981114X19-1	14	11	STRANDED	.025	.060	.620
98121419-1	14	12	SOLID	.025	.060	.597
981214X19-1	14	12	STRANDED	.025	.060	.635
98161419-1	14	16	SOLID	.025	.060	.660
981614X19-1	14	16	STRANDED	.025	.060	.702
98201419-1	14	20	SOLID	.025	.060	.737
982014X19-1	14	20	STRANDED	.025	.060	.779
982114X19-1	14	21	STRANDED	.025	.060	.790
These values are nominal in accordance with industry standards. Additional gauges and conductor count are available. Additional color code and State specs available upon request						



FALCON FINE WIRE AND WIRE PRODUCTS, INC.
2401 DISCOVERY BLVD • ROCKWALL, TEXAS 75032
214-771-3441 • 972-722-9168 • falconwire@aol.com



